Product data sheet

ESD adhesive tape with ESD warning symbol, transparent, 36 m

EN | 2026-11-12



Item numbers: 4 · see variant table

Transparent ESD adhesive tape with ESD warning symbol and a surface resistance of 10^5 to 10^9 ohms. Roll length 36 m, widths from 12 to 48 mm, diameter 76 mm.

Description

A see-through tape that leaves labelling visible and marks ESD packaging.

Transparent tape is suitable if labels, barcodes or lettering on the packaging are to remain legible. The printed ESD warning symbol still marks the goods.

According to the specification, the surface resistance is 10^5 to 10^9 ohms, i.e. in the dissipative range. The roll is 36 m long and has a diameter of 76 mm.

Typical areas of use

- Covering labels and barcodes
- Closing ESD bags
- Carton closure in shipping
- Fixing documents to containers

What to look for when choosing

- Resistance: surface resistance 10^5 to 10^9 ohms.
- Appearance: transparent, so labelling remains legible.
- Width: available from 12 mm to 48 mm.

Technical data

Variants	4 (item numbers see table)
Diameter	76 mm
Further details	Surface resistance 10^5~10^9 ohms
Supply	on request, quotation with price and pack size

Notes on use

Unroll the tape only at the grounded workstation, ideally with an ESD dispenser. Stick it on packaging, not on components. Store partly used rolls dust-free.

Frequently asked questions

Related: ESD workstation equipment · All ESD products · ESD basics

View datasheet (web page, German)

Variants

Format	Item number
12mm	DSWL47279
18mm	DSWL47280
24mm	DSWL47281
48mm	DSWL47282

Compiled from the product information. This data sheet does not replace a test certificate. The original documents are authoritative.